alleuroparts



DEC '18

Exclusive All Euro Special KABO Torque Wrenches

Kabo Torque Wrench | 3/8" Sq Drv 15–81 Ft Lbs



Kabo Torque Wrench | 1/2" Sq Drv 22-155 Ft Lbs



Kabo Torque Wrench | 1/2" Sq Drv 37 - 258 Ft Lbs



Imperial | 1/4" Sq Drv
•IMPERIAL 20 - 100 In Lbs



Metric | 1/4" Sq Drv •METRIC 2.25 - 11.3Nm



Ajax Ratcheting Breaker Bar 18" | 3/8" Sq Drv



Professional quality (ISO 6789), with calibration certificate (±3% accuracy).
•20–110Nm (15–81 Ft Lbs)



Professional quality (ISO 6789), with calibration certificate (±3% accuracy).
•30-210Nm (22-155 Ft Lbs)



Professional quality (ISO 6789), with calibration certificate (±3% accuracy).

•50-350Nm (37-258 Ft Lbs)



Ratcheting Torque Wrench Imperial | 1/4" Sq Drv



Ratcheting Torque Wrench Metric | 1/4" Sq Drv



Ajax Ratcheting Breaker Bar 18" | 3/8" Sq Drv



alleuroparts



DEC'18



alleuroparts



DEC ':



www.alleuroparts.co.nz 0800 255 387 parts@alleuroparts.co.nz

*Prices Valid until 15th January 2019

www.alleuroparts.co.nz 0800 255 387 parts@alleuroparts.co.nz

*Prices Valid until 15th January 2019


alleuroparts



Exclusive All Euro Preorder AST5188

Auxiliary Belt Tensioner Tool Set - 1.4 / 1.5 / 1.6 / 2.0 Diesel Engines FORD - PSA





Please Note: This Tool is exclusively available as a preorder - estimated delivery 3 weeks.

The Auxiliary Belt Tensioner Set has been developed to provide a safe and controlled method of adjusting the belt tensioner position during removal and installation of the auxiliary belt.

Belt tension is provided by a heavy spring built in to the tensioner unit, the tensioner features a raised peg as a location to apply leverage when removing or installing the auxiliary belt. Without the use of special tooling, belt removal or installation requires two people.

Access to the tensioner can be severely limited by engine and vehicle body components. AST5188 has been designed to provide easy access to the tensioner peg in all instances. The set includes a number of adaptors and an extension bar featuring two bi-hexagonal drives, providing a number of options when assembling the tool to access the tensioner.

AST5188 can be used with AST4765 Auxiliary Belt Tensioner Tool Set for even greater application coverage.

Also used on 2.0 / 2.2 DW10 and DW12 engines.

Applications:

Citroën 1.4 / 1.6 HDi 8v. / 16v. C1 / C2 - C3 III, C3 Pluriel, C4 Picasso Ford 1.4, 1.5, 1.6 TDCi / ECOnetic 8v. / 16v. - B-MAX, C-Max, EcoSport, Fiesta, Focus Focus C-Max - Fusion, Galaxy, Grand C-Max, Mondeo, S-MAX, Tourneo Connect

Tourneo Courier, Transit Connect, Transit Courier

Mazda 1.4 / 1.6 TDCi 8v. / 16v.- 2 (DE/DH), 3 (BK/BL),

Mini, 1.6 16v. - Mini Clubman, Mini Cooper, Mini One, R55/R56

Peugeot 1.4 / 1.6 HDi 8v. / 16v. - 1007, 107, 206, 206 CC, 206 SW, 307, 307 SW, 508

Toyota 1.4 DiD 8v. - Aygo

Volvo 1.6 D4 16v. - C30, S40, S80, V50, V70

AST5188