

## Wheel Hub Cleaning Tool & Discs ET4070 + ET4070D

## Wheel Bolt Face Cleaner Tool ET4074



For optimal cleaning  
of wheel hubs &  
brake discs

ET4070



Additional  
discs  
available

ET4070D



ET4074

For optimal cleaning of wheel hubs / brake discs on passenger cars / vans.

If the wheel hub isn't clean enough new brake discs will have uneven contact - this tool creates a perfect mounting surface for new brake discs

Inner dia: 90mm. Max speed: 1,500 RPM

Ideal for quick cleaning / corrosion removal of car wheel hubs with stud bolts up to 40mm diameter.

Replacement abrasive discs available (ET4074-D).

Use with cordless drill  
3/8" Sq Drv adaptor included  
Max speed: 1500 RPM

## Cleaning Brush Set DA1130

## Hub Nut Socket Toyota ET1457A



A versatile  
cleaning brush set.

DA1130



Solid pins for  
increased durability

ET1457A

Versatile cleaning brush set comprising brushes with brass | nylon | steel bristles respectively. Ideal for general cleaning tasks such as removing carbon, dirt, rust, paint etc

Brass | Nylon | Steel bristles  
180mm length

Professional quality four pin front wheel bearing socket for Toyota Hiace (06-) vehicles. The pins in this socket are solid / high quality for extra durability. Be careful to avoid sockets with cheaper split pins that will more easily fail under stress.

1/2" Sq Drv  
4 pin design



## O Ring Seal Picks ET1228

O Ring  
Removal Kit



ET1228

Hook set suitable for removing o-rings, sealing rings, rotary shaft seals etc. The rounded tips avoid damaging / scratching components. Can also be used to help push hoses over flanges (for instance, on turbochargers).  
2x straight, 2x offset (short & long)  
Blade length: 60mm & 135mm

## OBD2 Battery Saver ET5484

Save vehicle memory  
when changing  
batteries



ET5484

Save vehicle memory when changing batteries. Simply connect the cable to vehicle's OBDII port, and the other end to 12V power source.

## Spring Compressor HCBA1047



Use for BMW, Ford, VW,  
Audi, Saab, Volvo,  
Nissan, Honda + more



A Top Quality Tool  
- Built to Last. As Good as  
any European made tool  
Made in Taiwan

HCBA1047

\*Spring Specification:  
A:ø190-ø140 B:ø140-ø110 C:ø110-ø75  
\*Application: BMW, Toyota, Ford, Mitsubishi, VW, Audi, Saab, Nissan, Honda, Accord, Subaru, Volvo, Opel, Porsche.  
Contains -  
1. 453 mm (l) compressor bar, phosphate coated, max. Capacity: 300 mm ± 5 mm  
2. Small "u" style forks, phosphate coated: 65-125 mm  
3. Medium "u" style forks, phosphate coated: 88-160 mm  
4. Large "u" style forks, phosphate coated: 126-212 mm  
5. Ext block, phosphate coated: 64 mm (l) x 40 mm (w)

## Stretch Rib Belt Tool Kit HCBA1781

Also suitable for use  
with double belt drives



HCBA1781

\* Allows damage free mounting of flexible multi-ribbed belts.  
\* For the straightforward removal and fitting of new flexible V-ribbed belts (e.g. air-conditioning compressor).  
\* Also suitable for use with double-belt drives.  
- BMW 118, 120, 318, 320, 325, 330, 335, 520, 525, 530, 535, 635, 720, X3, X5  
- Audi A3 1.6/ 2.0D  
- Volkswagen Eos, Golf, Passat, Polo, Scirocco 2.0D plus Citroen, Volvo Peugeot and more

## Glow Plug Adaptor Set ET0801

Useful for pressure  
loss diagnosis



can also be used as  
adaptors for  
compression testers

ET0801

These pneumatic adaptors are designed to screw into glow plug bores, and fill the combustion chamber with compressed air. This is necessary when removing / installing valve springs on installed cylinder heads, or for pressure loss diagnosis.  
Sizes: M8 x 1.0 | M10 x 1.0 | M10 x 1.25  
3 Pce set

## Black Snake Angle Impact Wrench RMAX-IMP12A

Light & powerful  
Great for tight spaces



RMAX-IMP12A

Lightweight, powerful unit to get into the tightest of spaces. Composite handle. One hand forward / reverse.  
113 L/min avg air consumption  
88mm length  
1.19kg  
Torque Range: 27-231Nm / 20-170 Ft-Lbs

## Front Engine Back to Back Mount/Subframe Bush Tool VW HCBA1544

A timesaving  
workshop tool



HCBA1544

A comprehensive / specialised kit for servicing the two part engine support steady bar bush that is fitted to the front subframe of certain VAG models. This is a commonly overlooked mount that wears and causes vibrations through the vehicle & knocking under acceleration. This kit allows for sealing off the side of the aperture to enable easy extraction / insertion of the bushes, as well as allowing this task to be done without removing the subframe from the vehicle.  
A time saving workshop tool.

## Toyota Rear Axle Suspension Bush Tool - HCBB1623

Only 1 left  
in stock!



HCBB1623

For use with all common  
Toyota Bushes

A specialised tool for removing/installing the rear suspension bush on many popular late model Toyota vehicles. A time-saving tool!

Applications:  
Altis | Camry | Corolla | Previa | Yaris  
OEM bushes:  
48725-28050-S | 48725-12570 | 48725-0D040  
This tool saves heaps of time and headaches a must for garages who do a lot of work on Toyotas



## Professional Timing Light ET2042

Professional  
Timing Light



ET2042

Tachometer: 249 to 9,990 RPM ( $\pm 1\%$  Accuracy)  
Dwell: 0i to 180i / 2 - 12 cylinders ( $\pm 1\%$  Accuracy)  
Voltage: 10 - 16V DC ( $\pm 1\%$  Accuracy)  
Advance Degrees (2 / 4 cycle DIS & Conventional):  
0i to 90i ( $\pm 0.5i$  Accuracy)

## Radiator Pressure Kit Deluxe ET1039

A comprehensive kit  
Adaptors for  
almost all car types.



ET1039

The most comprehensive kit available. Includes vacuum purge / refill tool.

Adaptors for almost all cars.

## Test Light and Volt Meter ETPP5

Low Current  
- safe to use with  
electrical components



ETPP5

Integrated test light / voltmeter.

This meter draws very low current making it safe to use around delicate electronic components.

Includes interchangeable probes, leads and clips with 4mm banana connectors.

3 - 48V DC range

## Nitto Style Airline Kit 70 Pce Sonsbeek 100400KIT

Sonsbeek  
70 pce kit



100400KIT

Popular selection of Nitto Style couplers / adaptors, brass fittings & hose clamps.

- 1/4" BSP Female coupler (2x)
- 1/4" BSP Male coupler (5x) 3/8" Tail coupler (4x)
- 1/4" BSP Male adaptor (15x)
- 3/8" BSP Male adaptor (5x)
- 1/4" BSP Female adaptor (5x) 3/8" Tail adaptor (5x)
- 1/4" x 1/4" BSP Hex nipple (5x)
- 3/8" Tail x 1/4" BSP Male Tailpiece
- 10 - 16mm Worm Drive clamps (20x)