

## New Specialist Auto Tools

### Universal Locking Ring Tool HCBA1641

Makes dismantling and mounting of wheel bearing lock rings very easy. Designed to fit the larger lock rings - eg. the lock ring on the axle shaft.

\* The adjusting screw has a ¼ " ratchet grip which easily removes stuck and rusted lock rings. The grip angle between the tips is always correct. This makes the tool safer, more effective and easier to use than ordinary pliers. - Includes 3 kinds of specially designed tips - A1641-025 Circlip pin 2.5 mm, 2 pcs, A1641-030 Circlip pin 3 mm, 2 pcs  
A1641-035 Circlip pin 3.5 mm, 2 pcs



### VAG Clutch Removal Kit 7spd DSG ET1804

All the tools required to rebuild, repair & service the gearbox on 7 spd dual clutch gearbox OAM.  
Includes Gearbox Mechatronic Unit Lever  
Used to operate the engaging lever during dismantling and mounting of the mechatronic unit on 7 speed dual clutch gearbox OAM.  
Suitable for Audi SKoda and VW.

To Hire  
or Buy



### BMW/Diesel Engine Timing Tool- HCBC1421

Includes camshaft setting plate, flywheel locking pin & crankshaft turning tool.  
plus HP pump sprocket reatining tool required during pump removal & replacement.  
Applications: 2.0 N47 & 3.0 N57 Suits all applications and power variants, from 2007 up to 2011 models.

To Hire  
or Buy



[www.alleuroparts.co.nz](http://www.alleuroparts.co.nz) - 0800 255 387 - [parts@alleuroparts.co.nz](mailto:parts@alleuroparts.co.nz)



## New Specialist Auto Tools

### Benz & BMW Fan Service Wrench Kit HCBA1022

1 - BMW viscous fan nut wrench (32mm)

Removes lock nuts on thermo-viscous fans found on Ford, BMW... etc.

2 - BMW Pulley Holder

To hold the water pump pulley in place while loosening the radiator fan.

3 - Mercedes- Benz fan clutch wrench (65mm)

Special open-ended spanner allows removal and replacement of the radiator fan hub.

Application Mercedes Engines M103 (6cyl) M104 (6 cyl 4 valve) ZM119 (8 Cyl 4 valve)




### VAG Vibration Damper Assembly Tool - ET0037A

- OEM Equiv T10531

- Used for dismantling and assembling the vibration damper on 4 Cyl. 1.8L, 2.0L, 4v TSFI direct injection engine (Timing Chain)

Includes - Counterhold Tool, Tensioning pins Turning over tool, Knurled Nut



### BMW Ball Joint Puller- HCBB1294

(24mm & 27mm & 31mm & 36mm)

For Quick & easy separation of Ball joint connections.

Application: BMW E38, E39, E52, E53, E60, E61, E70, E83, E90, E91, E92, R50, R52, R53, RR1, RR2, X5. Mercedes E-Class (W211), CLS (W219), S-Class (W220) & SL(W230) Porsche 996, Audi A4, Audi A6. Land Rover 4000cc (V8)



[www.alleuroparts.co.nz](http://www.alleuroparts.co.nz) - 0800 255 387 - [parts@alleuroparts.co.nz](mailto:parts@alleuroparts.co.nz)

